



| | |
|----------|---|
| 1 | Domestic cold water circuit inlet 1" Gas M |
| 2-4 | Heating return/To Generator 1"1/2 Gas F |
| 3 | Connection for instrumentation 1/2" Gas F |
| 5 | Lower fixed heat exchanger outlet 1" Gas F |
| 6 | Connection for instrumentation 1/2" Gas F |
| 7-8 | Heating return/To Generator 1"1/2 Gas F |
| 9 | Lower fixed heat exchanger inlet 1" Gas F |
| 10 | Electrical immersion resistance 1"1/2 Gas F |
| 11 | Connection for instrumentation 1/2" Gas F |
| 13-14 | Heating return/To additional generator/Heating delivery 1"1/2 Gas F |
| 16 | Connection for instrumentation 1/2" Gas F |
| 17-19-21 | From Generator/ Heating delivery 1"1/2 Gas F |
| 18 | Connection for instrumentation 1/2" Gas F |
| 20 | Domestic hot water outlet 1" Gas M |

| Model | Net Volume | Df | De | H | A | H1 | H2 | H3 | H4 | H5 | H6 | H7 | H9 | H11 | H12 | H13 |
|-------|------------|------|------|------|------|-----|-----|-----|-----|-----|------|------|------|------|------|------|
| | [liters] | | | | | | | | | | | | | | | |
| 500 | 421 | 650 | 850 | 1620 | 1665 | 230 | 247 | 260 | 533 | 629 | 744 | 841 | 1011 | 1231 | 1343 | 1360 |
| 600 | 503 | 650 | 850 | 1870 | 1915 | 230 | 247 | 260 | 582 | 695 | 855 | 915 | 1144 | 1382 | 1593 | 1610 |
| 800 | 738 | 790 | 990 | 1840 | 1895 | 248 | 265 | 278 | 584 | 690 | 762 | 823 | 1115 | 1332 | 1541 | 1558 |
| 1000 | 855 | 790 | 990 | 2130 | 2180 | 248 | 265 | 284 | 656 | 787 | 953 | 998 | 1309 | 1588 | 1831 | 1843 |
| 1250 | 1131 | 900 | 1100 | 2202 | 2262 | 296 | 313 | 326 | 705 | 835 | 884 | 986 | 1357 | 1586 | 1879 | 1896 |
| 1500 | 1324 | 950 | 1150 | 2250 | 2315 | 296 | 313 | 336 | 736 | 845 | 1006 | 1061 | 1377 | 1653 | 1909 | 1921 |
| 2000 | 1829 | 1100 | 1300 | 2320 | 2400 | 330 | 347 | 370 | 770 | 879 | 1001 | 1060 | 1411 | 1687 | 1943 | 1955 |